

# HEADSETS COMPATIBILITY



Models	Ø	Concept		Dimensions of frame's head tube					Bearings	Stack height
		Technology		Ø ext	Tolerance	Ø int	Tolerance	Angular contact		
<b>Light'in Gold</b>	1" 1/8	Integrated	100 % integrated	46 mm	± 0,1 mm	42 mm	± 0,1 mm	45°	Ceramic	<b>10,3 mm</b>
<b>Light'in Ca</b>	1" 1/8	Integrated	100 % integrated	46 mm	± 0,1 mm	42 mm	± 0,1 mm	45°	Sealed bearing	<b>17 mm</b>
<b>Light'in St</b>	1" 1/8	Integrated	100 % integrated	46 mm	± 0,1 mm	42 mm	± 0,1 mm	45°	Cartridge	<b>7 mm</b>
<b>RAZ Gold</b>	1" 1/8	Semi integrated	Integrated cups	50 mm	± 0,1 mm	44 mm	0/-0,05	\	Ceramic	<b>12,9 mm</b>
<b>RAZ ca</b>	1" 1/8	Semi integrated	Integrated cups	50 mm	± 0,1 mm	44 mm	0/-0,05	\	Sealed bearing	<b>18 mm</b>
<b>RAZ St</b>	1" 1/8	Semi integrated	Integrated cups	50 mm	± 0,1 mm	44 mm	0/-0,05	\	Cup cartridge	<b>9 mm</b>
<b>O'light Lx</b>	1" 1/8	Cups	Aheadset	40 mm	± 0,1 mm	34 mm	0/-0,05	\	Sealed bearing	<b>26 mm</b>
<b>O'light R</b>	1" 1/8	Cups	Aheadset	40 mm	± 0,1 mm	34 mm	0/-0,05	\	Cartridge	<b>35 mm</b>
<b>O'light St</b>	1" 1/8	Cups	Aheadset	40 mm	± 0,1 mm	34 mm	0/-0,05	\	Cartridge	<b>27,5 mm</b>
<b>A9</b>	1"	Cups	Thread	35 mm	± 0,1 mm	30,2 mm	0/-0,05	\	Needle bearings	<b>38 mm</b>
<b>A9 St</b>	1"	Cups	Thread	35 mm	± 0,1 mm	30,2 mm	0/-0,05	\	Ball bearing	<b>39,4 mm</b>